

FLAT BODY CYLINDER

Part Number	Capacity (tons)	Stroke (in)	Oil Capacity (in3)	Collapsed Height (in)	Extended Height (in)	Outside Diameter (in)
CF5	5	0.25	0.25	1.28	1.53	2.31 x 1.63
CF10	10	0.44	0.98	1.69	2.13	3.25 x 2.19
CF20	20	0.44	1.94	2.03	2.47	4.00 x 3.00
CF30	30	0.50	3.25	2.31	2.81	4.63 x 3.75
CF50	50	0.63	6.01	2.63	3.25	5.50 x 4.50
CF75	75	0.63	9.94	3.13	3.75	6.50 x 5.50
CF100	100	0.63	12.27	3.38	4.00	7.00 x 6.00

FLAT BODY CYLINDER *continued*

Part Number	Rod Diameter (in)	Cylinder Bore (in)	Effective Area (in2)	Base to Advance Port (in)	Rod to Base (in)	Rod to Mounting Hole (in)	Hole Diameter (in)	Weight (lbs.)
CF5	1.00	1.13	0.99	0.63	0.81	0.88	0.20	2.3
CF10	1.50	1.69	2.24	0.75	1.09	1.34	0.28	3.1
CF20	2.00	2.38	4.43	0.75	1.56	1.56	0.40	6.8
CF30	2.50	2.88	6.49	0.75	1.88	1.75	0.40	10
CF50	2.75	3.50	9.62	0.75	2.25	2.13	0.47	15
CF75	3.25	4.50	15.90	0.75	2.75	2.63	0.53	25
CF100	3.63	5.00	19.63	0.75	3.00	2.94	0.53	32

DESCRIPTION

- Low profile, high tonnage steel construction.
- Single acting heavy duty spring return.
- Grooved plunger ends.
- 3/8" NPTF high flow coupler with dust caps.
- Exterior finish powder painted and ANSI B30.1 compliant.

