

# LOW PROFILE (SHORT) CYLINDERS

## LOW PROFILE (SHORT) CYLINDERS

Part Number	Capacity (tons)	Stroke (in)	Oil Capacity (in <sup>3</sup> )	Collapsed Height (in)	Extended Height (in)	Outside Dia. (in)	Rod Dia. (in)
CL10-1	10	1.50	3.35	3.47	4.97	2.75	1.50
CL20-2	20	1.75	7.75	3.88	5.63	3.88	2.00
CL30-2	30	2.44	15.82	4.63	7.06	4.50	2.62
CL50-2	50	2.38	22.85	4.81	7.19	6.25	2.75
CL100-2	100	2.50	44.18	5.56	7.81	8.38	3.63

## LOW PROFILE (SHORT) CYLINDERS continued

Part Number	Bore Dia. (in)	Effective Area (in <sup>2</sup> )	Bolt Circle (in)	Thread	Thread Depth (in)	Weight (lbs.)
<b>Base Mounting Holes</b>						
CL10-1	1.69	2.24	1.03	M4	0.32	9
CL20-2	2.38	4.43	1.56	M5	0.32	11
CL30-2	2.88	6.49	1.56	M5	0.32	15
CL50-2	3.50	9.62	1.56	M5	0.32	24
CL100-2	5.00	19.63	2.19	M8	0.40	50

### DESCRIPTION

- Single acting, steel construction, heavy duty spring return.
- Compact low profile design.
- Collar threads with protective cover & base mounting holes.
- 3/8" NPTF high flow coupler with dust caps.
- Exterior finish powder painted and ANSI B30.1 compliant.

