

## PRESSURE GAUGES

Part Number	Face Diameter (in)	Port Size, Mount & Fill	Pressure Range (psi)	Pressure Range (bar)
GV25D	2.5	1/4" NPT, lower & no fill	0 - 10,000	0 - 700
GV40D	4			
GV25L	2.5	1/4" NPT, lower & liq. filled		
GV40L	4			



## HYDRAULIC HOSES

Part Number	Diameter (in)	Length (ft)	Operating Pressure (psi)
HA25-3	1/4"	3	10,000
HA25-6	1/4"	6	
HA25-10	1/4"	10	
HA25-20	1/4"	20	
HA38-6	3/8"	6	
HA38-10	3/8"	10	
HA38-20	3/8"	20	
HA-38-50	3/8"	50	



### DESCRIPTION

- Hoses are MSHA approved.
- Neoprene cover is resistant to abrasion, oil, and weather.
- Temperature range of -40° to +250°F.

Hose shown with optional couplers



## HIGH FLOW COUPLERS

Part Number	Size	Operating Pressure (psi)	Type
HFC-F-375	3/8"	10,000	Female
HFC-M-375	3/8"	10,000	Male
HFC-375	3/8"	10,000	Set

### DESCRIPTION

- Designed for higher flow capacity and lower pressure losses than standard couplers.
- Threaded union design allows for fast component changes.
- Couplers permit safe separation at zero psi, with minimal oil loss.