

# Air Over Hydraulic Pumps



PA9 shown with optional air fitting.

**PA9 SERIES**

## AIR OVER HYDRAULIC PUMPS - PA9 SERIES

Part Number	Pressure Rating (psi)	Usable Oil (in3)	Flow rate in3/min		Reservoir Construction	Use with Cylinder	Weight (lbs.)
			No Load	10,000 psi			
PA9-37	10,000	37	132	16	aluminum alloy	S/A	12
PA9-61		61					16

## AIR OVER HYDRAULIC PUMPS - PA6 SERIES

Part Number	Pressure Rating (psi)	Usable Oil (in3)	Flow Rate in3/min		Reservoir Construction	Use with Cylinder	Weight (lbs.)
			No Load	10,000 psi			
PA6-98B	3,500	98		48	cast aluminum	S/A	20
PA6-98C		98		13	cast aluminum		16
PA6-122	10,000	122	82	13	aluminum alloy	S/A	20
PA6-98R		98					23
PA6-231		231					32
PA6-122D		122				D/A	22
PA6-231D		231					32
PA6-460D		460					44

### DESCRIPTION

- Air Hydraulic Turbo speed operation offering high flow at high pressure.
- Hydraulic port swivels for easy connection.
- Air pressure range 40-170 PSI.
- PA9 with mounting plate to be securely fastened.
- PA9 pumps can work in horizontal or vertical position.
- Pressure relief valve for overload protection.



**PA6-98C**



**PA6-98R**



**PA6 SERIES**