

Center Hole Cylinders

Part Number	Capacity (tons)	Stroke (In.)	Oil Capacity (In ³)	(A) Collapsed Height	(Y) Center Hole Dia.	(B) Extended Height	(W) Outside Dia. (in.)	Outside Collar Thread	Inside Collar Thread	(J) Rod Dia. (In.)
CH12-0	12	0.31	0.9	2.36	0.77	2.68	2.87	2-3/4"-16"	3/4"-16"	2.09
CH12-2	12	2	4.8	4.72	0.77	6.38	2.87	2-3/4"-16"	3/4"-16"	2.09
CH12-3	12	3	8.7	7.24	0.77	10.24	2.87	2-3/4"-16"	3/4"-16"	2.09
CH20-2	20	2	8.9	6.38	1.06	8.35	3.88	3-7/8"-12"	1-9/16"-16"	2.13
CH20-6	20	6	8.9	6.38	1.06	8.35	3.88	3-7/8"-12"	1-9/16"-16"	2.13
CH30-2	30	2	18.6	7.01	1.31	9.53	4.50	4-1/2"-12"	1-13/16"-16"	2.50
CH30-6	30	6	45.3	12.99	1.31	19.11	4.50	4-1/2"-12"	1-13/16"-16"	2.50
CH60-3	60	3	41.4	9.75	2.12	12.74	6.25	6-1/4"-12"	2-3/4"-16"	3.50
CH60-6	60	6	83.4	12.74	2.12	18.77	6.25	6-1/4"-12"	2-3/4"-16"	3.50
CH100-3	100	3	66.3	10.00	3.11	13.00	8.38	8-3/8"-12"	4"-16"	5.00
CH100-6	100	6	132.8	23.42	3.11	29.33	8.38	8-3/8"-12"	4"-16"	5.00

DESCRIPTION

- Single acting, steel construction, heavy duty spring return.
- Threaded collar, threaded rod & base mounting holes for easy fixturing.
- 3/8" NPTF port with high flow coupler and dust cap.
- Hollow chrome plated rod design allows for both, pull and push forces.
- Durable exterior finish and ANSI B30.1 compliant.

